

# IPC-T24-L

IPC-T24-L



## Dome IP 4MP Smart Dual Light outdoor dome



- Vesta Advanced Video IP Dome
- 4MP@25/30ips, H.265
- 0.006 lux, Smart Dual Light 20-30m
- 2.8mm fixed optical
- Digital WDR, 3D-NR
- Perimeter protection and intelligent motion detection
- Built-in microphone
- MicroSD slot, RJ45, Onvif, IP67, 3AXIS, PoE.



Reference / Model	IPC-T24-L / IPC-T24-L
4 megapixel 1/2.7" CMOS sensor	
H.265, H.264 video formats	
Up to 4MP resolution	
Stream 1: 4MP (1~25/30 fps)	
Stream 2: D1 (1~25/30 fps)	
Stream 3: 720P (1~25/30 fps)	
Day/Night Mode	
Smart Dual Light: 1 IR led (30 meters) + 1 warm light led (20 meters)	
0.006 lux, 0 lux when light is on	
2.8 mm fixed optics	
Image modes: BLC, HLC, digital WDR, 3D-NR, Mirror.	
White balance	
Automatic and manual gain control	

## Dome IP 4MP Smart Dual Light outdoor dome

Reference / Model	IPC-T24-L / IPC-T24-L
	4-Zone video sensor and 4-Zone privacy mask
	Perimeter protection with cross-line detection and intrusion detection (supports person/vehicle classification)
	Intelligent motion detection
	Built-in microphone
	MicroSD card slot (card not included)
	Network interface: RJ45 (10/100 Base-T)
	Network protocols: TCP/IP, UDP, HTTP, DHCP, DDNS, FTP, UPNP
	Onvif, CGI, P2P, SDK and API support
	Compatible with IE8 and later browsers
	Management software
	Compatible with IOS and Android mobile devices
	Power supply: 12V DC / PoE (802.3af)
	Maximum power consumption: 3W
	Storage temperature from -40°C ~ +60°C
	Operating temperature from -30°C ~ +60°C
	Operating relative humidity <95%.
	IP67 degree of protection
	Plastic housing
	Dimensions: Ø110 x 97 mm
	Net weight: 430 g