

IP CCTV / Professional IP cameras / Uniview - Uniarch / Bullet Cameras

UV-IPC-B134-AF28-ECO

UNIARCH



Features

- Uniarch
- Bullet IP camera
- 1/3.0" CMOS
- 4 Megapixel (2560x1440)
- 2.8 mm Lens
- 0.01 Lux
- IR Range 30 m
- Compression Ultra265/H.265/H.264
- RJ45 10 M/100 M Base-TX Ethernet
- PoE IEEE 802.3af
- Weatherproof IP67
- IR Cut
- Web interface, CMS, Smartphone & NVR
- ONVIF compatible

Specifications

Range	Uniarch
Image sensor	1/3.0" CMOS
Day / Night	Mechanical ICR filter
Maximum resolution	4 Megapixel (2560x1440)
Lens	2.8 mm
FOV	Horizontal: 87.8° Vertical: 48.9° Diagonal: 99°
Range performance	Detect: 51.4 m Observe: 20.6 m Recognize: 10.3 m Identify: 5.1 m
Main Stream rate	4 MP (2560x1440)@30fps 1080P (1920*1080)@30fps 720P (1280*720)@30fps
Extra Stream rate	640*360@30fps 2CIF(704*288)@30fps CIF(352*288)@30fps
Compression	Ultra265/H.265/H.264
WDR	DWDR
Minimum illumination	0.01 Lux (Colour) 0 Lux with IR
Infrared range	30 m
Image improvements	DWDR, AGC, 2D/3D-DNR, ROI, Privacy Mask, Smart IR
Internal memory	Does not have
Alarms	Does not have
Audio	Built-in microphone
Network interface	Ethernet 10/100 BaseT
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Power supply	2.5 W, PoE IEEE802.3af
Interoperability	ONVIF, API, SDK
Temp. operation	-30° C ~ 60° C
Degree of protection	Weatherproof IP67

Dimensions	65 (H) x 61 (W) x 140 (D) mm
Weight	150 g
Material	Plastic