

IP CCTV / Professional IP cameras / Uniview - Uniarch / Bullet Cameras

UV-UHO-B1R-M2F4

UNIARCH



Features

- Uniarch
- IP camera
- 1/2.9" Progressive Scan CMOS
- 2 Megapixel (1920x1080)
- 4 mm Lens
- 0 Lux
- IR Range 30 m
- Compression Ultra265/H.265/H.264
- RJ-45 10/100 BaseT
- Wifi IEEE802.11b/g/n
- Weatherproof IP67
- IR Cut
- Built-in microphone
- WDR 120dB
- MicroSD 128GB
- 3-Axis

Specifications

Brand	Uniarch
Image sensor	1/2.9" Progressive Scan CMOS
Maximum resolution	2 Megapixel (1920x1080)
Lens	4 mm
Main Stream rate	1080P (1920 x 1080), Max 30fps; 720P (1280 x 720), Max 30fps;
Extra Stream rate	720P (1280 x 720), Max 30fps; D1 (720 x 576), Max 30fps; 640 x 360,Max 30fps; 2CIF(704 x 288), Max 30fps; CIF(352 x 288), Max 30fps;
Compression	Ultra 265, H.265, H.264, MJPEG
Minimum illumination	Colour: 0.01 lux (F2.1 AGC ON) 0 lux with IR on
Infrared range	30 m
Image improvements	DWDR, BLC, HLC, AGC, 2D/3D-NR, Motion detection, ROI, Privacy Mask
Day / Night	Mechanical ICR filter
Internal memory	MicroSD card, Max 128 GB
Alarms	Does not have
Audio	Built-in microphone
Detection functions	Human body detection, Motion detection, Audio detection, Anti-tampering alarm.
Wi-Fi	IEEE802.11b/g/n
Wi-Fi frequency range	2.4 GHz ~ 2.4835 GHz
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Power supply	DC 12V / 3,6W
Temp. operation	-30° C ~ 60° C
Degree of protection	Weatherproof IP67
Dimensions	168 (H) x 88 (W) x 72 (H) x [%VAR%] (D) mm
Weight	280 g